



Door Operators ➤ Automatically the best choice

www.linkcontrols.co.uk

NEW Range - Comfort 360, 370, 380

Operator Model	Push & Pull Force (N)	Door Travel Speed (mm/s)	Power Input Standby (W)	Illuminant	Extendable to
Comfort 360	650	220	<0.6 W blue line	2 x 10 LED : 80 W	160 W
Comfort 370	850	235	<0.6 W blue line	2 x 10 LED : 80 W	160 W
Comfort 380	1100	180	<0.6 W blue line	2 x 10 LED : 80 W	160 W



blueline

[E O S] EASY OPERATING SYSTEM
 MSBUS



blueline

[E O S] EASY OPERATING SYSTEM
 MSBUS

More functions. More clarity. More speed. More light.
 More performance. More design. Less energy consumption.

Flexible installation with a power head that can be rotated

[E O S] EASY OPERATING SYSTEM

One for all

Marantec operator systems are activated using the uniform programming structure. This saves time and simplifies the installation of different operators.



Width: 48 mm
 Height: 88 mm
 Depth: 14 mm
 Weight: 0,08 kg

blueline



More speed (up to 235 mm/sec)
 and less energy consumption at once

MSBUS

External programming device Command 108
 with 3 m connecting cable with BUS connector

Marantec BUS-System

- Easy cabling with coded system plug
- Self-detection(plug and play) of connected modules
- Permanent function control of all BUS devices
- Easy function programming either directly on the control or with the external programming device
- Central failure notification of all moduls on the control



Completely integrated battery back-up system
 (Optional extra)