

**Hormann
V 5015 SEL,
V 5030 SEL**



**EMAIL: ENQUIRIES@SAMSONDOORS.CO.UK
TELEPHONE: (01933) 448850
MON - FRI 8:30AM - 5:30PM**

Flexible High-Speed Doors

Internal doors with SoftEdge and anti-crash



Door type V 5030 SEL

The spring steel wind locks increase the curtain stability and withstand stronger draughts.
(Figure shows a door with an optional aluminium bottom profile for wind class 1)



Door type V 5015 SEL

The proven door for draught-free areas: the aluminium profiles allow the curtain segments to be quickly and inexpensively replaced in case of repair. Insect screen instead of the vision panel also available on request.

Door type V 5015 SEL

From a height of 3000 mm, you can optionally receive the door with two vision panels for better visual contact during forklift traffic and thus greater safety.



Flexible High-Speed Doors

Internal doors with SoftEdge and anti-crash

Door type V 5015 SEL

The inexpensive internal door for areas without draught comes with safety functions such as SoftEdge and light grilles as standard. The aluminium wind lock also makes the door particularly service-friendly, since curtain segments can be quickly replaced if repairs are necessary. For an improved view the curtain is also available with two transparent curtain sections.

Door type V 5030 SEL

Draughts always pose a particular challenge for doors. With the robust wind locks made of spring steel, the V 5030 SEL remains stable under small pull and wind loads. You can also optionally obtain the V 5030 SEL with aluminium bottom profile for wind class 1 (DIN EN 12424).



V 5015 SEL
Curtain stability with aluminium profiles



V 5015 SEL
Optional fly-protection curtain in place of the vision panel



V 5030 SEL
Spring steel wind lock for quiet door travel

V 5030 SEL

Optional with aluminium bottom profile for wind class 1

Features

Door type	V 5015 SEL	V 5030 SEL
Suitable application	Interior	Interior
Size range		
Max. width (mm)	5000	5000
Max. height (mm)	5000	5000
Speed with control	BK 150 FU E-1	BK 150 FU E-1
Max. opening (m/s)	1,5	2,0
Closing approx. (m/s)	0,8	0,8
Curtain	UPVC, aluminium profiles	UPVC, spring steel wind locks with lateral twin rollers
Temperature range	+5°C to +40°C	+5°C to +40°C
Fabric thickness (mm)	1,5	1,5
Vision panel thickness (mm)	2,0	2,0
Fly protection curtain	○	–
Curtain colours		
RAL 1018 Zinc yellow	●	●
RAL 2004 Pure orange	●	●
RAL 3002 Carmine red	●	●
RAL 5010 Gentian blue	●	●
RAL 7038 Agate grey	●	●
Emergency opening		
Emergency crank handle	●	●
Emergency hand chain	○	○
Automatic door opening via UPS in case of power failure	○	○

● = Standard ○ = Optional

All colours are based on RAL.

Curtain colours




RAL 1018
Zinc yellow




RAL 2004
Pure orange



RAL 3002
Carmine red



RAL 5010
Gentian blue



RAL 7038
Agate grey

SAMSON



**6-8 MEADOW CLOSE
ISE VALLEY INDUSTRIAL ESTATE
FINEDON ROAD
WELLINGBOROUGH
NN8 4BH**

**EMAIL: ENQUIRIES@SAMSONDOORS.CO.UK
TELEPHONE: (01933) 448850
MON - FRI 8:30AM - 5:30PM**