

SECEUROBAR™

Removable Window Bar System

SPECIFICATION

SPECIFICATION EXTERNAL TUBE

19mm OUTSIDE DIAMETER STEEL TUBE
1.6mm WALL THICKNESS
100 Micron NYLON SPECTRA COAT
WEIGHT : 0.7 Kg/m

INTERNAL RE-INFORCING TUBE

15mm OUTSIDE DIAMETER STEEL TUBE
1.5mm WALL THICKNESS
ZINC FLO-COATED
WEIGHT : 0.52 Kg/m

LOCK

HIGH SECURITY 10 PIN RADIAL CAMLOCK
5 MILLION + KEY COMBINATIONS
AVAILABLE KEYED TO SUIT OR DIFFER
ANTI-DRILL CENTRE WITH 2 KEYS PER LOCK
KEYS CAN BE REMOVED IN THE LOCKED AND UNLOCKED POSITIONS

TOP & BOTTOM GUIDES

ALUMINIUM ALLOY EXTRUSIONS
POWDER COATED TO 60 Micron THICKNESS.
TOP GUIDE : 19.5mm HOLES
BOTTOM GUIDE : 13.5mm HOLES
WEIGHT : 0.9Kg/m

COLOURS

STANDARD COLOUR: SEMI GLOSS WHITE (RAL 9010)
OTHER COLOURS ARE AVAILABLE BY QUOTATION

BAR PITCH

127mm (CENTRE TO CENTRE)

ORIENTATION

BARS ARE HORIZONTAL OR VERTICAL.

All other metallic components are zinc coated for corrosion resistance.